

Patent Claims:

1. Hydraulic piston, in particular brake piston for an automotive vehicle brake, with a thermochemically treated surface,
c h a r a c t e r i z e d by several superposed layers at the piston surface, comprising:
 - a layer of oxide that is arranged directly at the piston surface and has a thickness of at least $1\mu\text{m}$,
 - a connecting layer which is arranged beneath the layer of oxide and is mainly composed of nitrides,
 - a diffusion layer that is arranged beneath the connecting layer and includes nitrogen in a dissolved condition or separated nitrides,
wherein the connecting layer has a minimum thickness of $8\mu\text{m}$.
2. Hydraulic piston as claimed in claim 1,
c h a r a c t e r i z e d in that the connecting layer includes capillary tubes which are respectively closed at the piston surface by portions of the layer of oxide.
3. Process for surface treatment of a hydraulic piston, in particular a brake piston,
c h a r a c t e r i z e d by the following procedure:

- 9 -

- nitrocarburization of the piston in a gaseous medium;
 - postoxidation of the piston in a medium yielding oxygen O_2 ;
 - machining of the oxidized surface for adjusting the surface quality.
4. Process for surface treatment of a hydraulic piston as claimed in claim 3,
c h a r a c t e r i z e d in that the nitrocarburization of the piston is carried out in several stages:
- a first stage wherein the piston is exposed to a first gaseous medium comprised of ammonia NH_3 , carbon dioxide CO_2 , and nitrogen,
 - a second stage of nitrocarburization wherein the piston is exposed to a second gaseous medium comprised of ammonia NH_3 and carbon dioxide CO_2 .
5. Process for surface treatment of a hydraulic piston as claimed in any one of claims 3 to 4,
c h a r a c t e r i z e d in that the temperature during the nitrocarburization process amounts to maximally $530^\circ C$.
6. Process for surface treatment of a hydraulic piston as claimed in any one of claims 3 to 5,

- 10 -

c h a r a c t e r i z e d in that an ambient medium separated from ammonia NH_3 is provided for the piston before the postoxidation.

7. Process for surface treatment of a hydraulic piston as claimed in any one of claims 3 to 6,
c h a r a c t e r i z e d in that machining is effected by a polishing or brushing operation.

1/25
(10)
(11)
(12)
(13)
(14)
(15)
(16)
(17)
(18)
(19)
(20)
(21)
(22)
(23)
(24)
(25)
(26)
(27)
(28)
(29)
(30)
(31)
(32)
(33)
(34)
(35)
(36)
(37)
(38)
(39)
(40)
(41)
(42)
(43)
(44)
(45)
(46)
(47)
(48)
(49)
(50)
(51)
(52)
(53)
(54)
(55)
(56)
(57)
(58)
(59)
(60)
(61)
(62)
(63)
(64)
(65)
(66)
(67)
(68)
(69)
(70)
(71)
(72)
(73)
(74)
(75)
(76)
(77)
(78)
(79)
(80)
(81)
(82)
(83)
(84)
(85)
(86)
(87)
(88)
(89)
(90)
(91)
(92)
(93)
(94)
(95)
(96)
(97)
(98)
(99)
(100)